



Shine Bright, Reflect Right
Upgrade with
Sunshield Reflective Films



www.cosmosunshield.com

#SPFforWindows #SafetyforWindows

COSMO SUNSHIELD REFLECTIVE FILMS

Where cutting-edge nano technology meets reflective elegance. Window films that offer metallic finish and mirror effect. Elevating any space with style and sophistication.

EXPLORE A SPECTRUM OF SHADES AND FINISHES

Tailored to blend comfort, privacy and aesthetics with your unique needs. Discover the potential of reflective window films and transform your windows effortlessly.



WHY SHOULD YOU CHOOSE SUNSHIELD REFLECTIVE FILMS?



Enhanced
daytime privacy



Enhances
aesthetic appeal



Resistant to
fading



Blocks more
than 99%
of harmful
UV radiation



Up to 10%
savings on
energy bills



Reduces
daytime
glare indoors



Blocks solar
heat to
boost comfort

LUSTER SERIES

REFLECTIVE


GOLD

CS-220-RGd-1580
2Ply 2Mil

Solar Properties

Visible Light Transmission	18%
Ultra Violet Rejected	>99%
Infra Red Heat Rejected	87%
Total Solar Energy Rejected	77%
Glare Reduction	80%
Shading Coefficient	0.27
SHGC (G-Value)	0.24

VISIBLE LIGHT TRANSMISSION



SOLAR ENERGY REJECTION



LUSTER SERIES

REFLECTIVE


BRONZE

CS-210-RBz-1585
2Ply 2Mil

Solar Properties

Visible Light Transmission	15%
Ultra Violet Rejected	>99%
Infra Red Heat Rejected	87%
Total Solar Energy Rejected	78%
Glare Reduction	83%
Shading Coefficient	0.25
SHGC (G-Value)	0.22

VISIBLE LIGHT TRANSMISSION



SOLAR ENERGY REJECTION



LUSTER SERIES

REFLECTIVE


SILVER

CS-420-PR-SL-2080
2Ply 2Mil

Solar Properties

Visible Light Transmission	20%
Ultra Violet Rejected	>99%
Infra Red Heat Rejected	86%
Total Solar Energy Rejected	73%
Glare Reduction	78%
Shading Coefficient	0.30
SHGC (G-Value)	0.27

VISIBLE LIGHT TRANSMISSION



SOLAR ENERGY REJECTION



LUSTER SERIES

REFLECTIVE


SILVER

CS-420-PR-SL-6050
2Ply 1.5Mil

Solar Properties

Visible Light Transmission	60%
Ultra Violet Rejected	>99%
Infra Red Heat Rejected	50%
Total Solar Energy Rejected	34%
Glare Reduction	33%
Shading Coefficient	0.74
SHGC (G-Value)	0.66

VISIBLE LIGHT TRANSMISSION



SOLAR ENERGY REJECTION





1st Floor, Uppal's Plaza, District Centre, M-6, Jasola, Delhi-110025

☎ 1800 57 00057 | ✉ sunshield@cosmofilms.com

🌐 www.cosmosunshield.com

January Edition-2025