

Cosmo Sunshield
Redefining Excellence in Window Films

High Heat Rejection Ultra Cool 7090

Maximum Thermal Comfort
Maximum Natural Light

Applications



Residential
Buildings



Commercial
Spaces



Office
Building



Railways
and Marine

Connect with us

☎ 1800 57 00057 | ✉ sunshield@cosmofilms.com

🌐 www.cosmosunshield.com



Ultra Cool 7090

Nano Ceramic Technology Ultra Cool 7090

SOLAR PROPERTIES

Visible Light Transmission	70%
Ultraviolet Rejected	>99%
Infra Red Heat Rejected	90%
Total Solar Energy Rejected	46%
Glare Reduction	22%
U-Value (W/m ² .K)	5.5

Also available with the option of safety in 4mil thickness

- Ultra Cool 7090 offers high VLT, which means more natural light can pass through film and glass combination.
- Infra Red Heat Rejected should be considered over Total Solar Energy Rejected if the purpose of fenestration is heat rejection.

Benefits



99% UV
Protection



Up to 10% Savings
on Energy Bills



90% IR Heat
Rejection



Glare
Reduction



Fade
Protection



Aesthetically
Pleasant Look

Connect with us

☎ 1800 57 00057 | ✉ sunshield@cosmofilms.com

🌐 www.cosmosunshield.com

