

Cosmo Sunshield
Redefining Excellence in Window Films

High Heat Rejection Ultra Cool 5095

**Filter Out Heat with
Maximum Natural Light**

Applications



Residential
Buildings



Commercial
Spaces



Office
Building



Railways
and Marine

Connect with us

☎ 1800 57 00057 | ✉ sunshield@cosmofilms.com

🌐 www.cosmoconsumer.com



Ultra Cool 5095

2Ply 1.5Mil

SOLAR PROPERTIES

Visible Light Transmission	51%
Ultraviolet Rejected	>99%
Infra Red Heat Rejected (900-1000)	94%
Infra Red Heat Rejected (780-2500)	92%
Total Solar Energy Rejected	51%
Glare Reduction	35%
Shading Coefficient	0.54
SHGC(G-Value)	0.48

Also available with the option of safety in 4mil thickness

- Ultra Cool 5095 offers high VLT, which means more natural light can pass through film and glass combination.
- Infrared Heat Rejected should be considered over Total Solar Energy.
- Rejected if the purpose of fenestration is heat rejection.

Benefits



99% UV
Protection



Up to 20% Savings
on Energy Bills



94% IR Heat
Rejection



Glare
Reduction



Fade
Protection



Aesthetically
Pleasant Look

Connect with us

☎ 1800 57 00057 | ✉ sunshield@cosmofilms.com

🌐 www.cosmoconsumer.com

